UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/617,186	07/09/2003	Hideki Hagiwara	393032038900	3003
David L. Fehrn	7590 08/23/2007		EXAM	INER
Morrison & Foerster LLP			FAULK, DEVONA E	
35th Floor 555 W. 5th Stre	set .		ART UNIT	PAPER NUMBER
Los Angeles, CA 90013			2615	
			MAIL DATE	DELIVERY MODE
			08/23/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
	10/617,186	HAGIWARA, HIDEKI				
Office Action Summary	Examiner	Art Unit				
	Devona E. Faulk	2615				
The MAILING DATE of this communication Period for Reply	appears on the cover sheet wi	th the correspondence address				
A SHORTENED STATUTORY PERIOD FOR RE WHICHEVER IS LONGER, FROM THE MAILING  - Extensions of time may be available under the provisions of 37 CF after SIX (6) MONTHS from the mailing date of this communication  - If NO period for reply is specified above, the maximum statutory pe  - Failure to reply within the set or extended period for reply will, by si Any reply received by the Office later than three months after the mearned patent term adjustment. See 37 CFR 1.704(b).	G DATE OF THIS COMMUNIC R 1.136(a). In no event, however, may a re to the state of	CATION.  eply be timely filed  THS from the mailing date of this communication.  EANDONED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 0	7 February 2007.					
,	, <del></del>					
, —	• • • • • • • • • • • • • • • • • • • •					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4)  Claim(s) 1,3-7,9-15 and 17-22 is/are pendiday of the above claim(s) is/are with 5)  Claim(s) is/are allowed. 6)  Claim(s) 1,3-7,9-15 and 17-22 is/are reject 7)  Claim(s) is/are objected to. 8)  Claim(s) are subject to restriction are	drawn from consideration.					
Application Papers						
9) The specification is objected to by the Exam 10) The drawing(s) filed on <u>09 July 2003</u> is/are: Applicant may not request that any objection to Replacement drawing sheet(s) including the co 11) The oath or declaration is objected to by the	a)⊠ accepted or b)☐ object the drawing(s) be held in abeyan rrection is required if the drawing	nce. See 37 CFR 1.85(a). (s) is objected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
<ul> <li>12)  Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a)  All b)  Some * c) None of:</li> <li>1.  Certified copies of the priority documents have been received.</li> <li>2.  Certified copies of the priority documents have been received in Application No</li> <li>3.  Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	Paper No(s	Summary (PTO-413) s)/Mail Date nformal Patent Application 				

Application/Control Number: 10/617,186

Art Unit: 2615

## **DETAILED ACTION**

## Response to Arguments

- 1. Applicant's arguments, filed 2/6/2007, with respect to the newly recited language in claims have been fully considered and are persuasive.
- 2. Claim 11 was indicated as allowable in the previous office action. The applicant has written claim 11 in independent form. The applicant has added new claims 19-22. Claim 19 recites similar language to claim 1.
- 3. Claims 2,8 and 16 are cancelled with the amendment filed on 2/6/2007...
- 4. The examiner has determined that there are some 112 issues that need to be addressed.

## Claim Rejections - 35 USC § 112

- 5. The following is a quotation of the second paragraph of 35 U.S.C. 112:
  The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 6. Claims 1-22 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.
- 7. Claims 1,11,15,17 and 19 recite adjusting, for each group, an amplification rate of all amplifiers involved in the same group according to the detected maximal signal level such as to decrease the amplification rate at the maximal signal level increases.

  The specification discloses, on page 18, paragraph 0024-poage 22, paragraph 00229' that

Art Unit: 2615

In FIG. 8(a), the reference numeral 60 denotes an absolute value and maximum value detection unit that holds a maximum value of absolute values of the input signals L.sub.H, I.sub.RH, I.sub.LSH, I.sub.RSH, I.sub.CH, and I.sub.LFEH within a specified time period. This held value becomes the maximum value of respective signal levels (envelopes) for the six signals. The reference numeral 70 denotes a gain control unit that determines a multiplier gain, i.e., a multiplier signal using the abovementioned maximum value as an input level according to a characteristic curve similar to that of FIG. 4. The reference numeral 80 denotes an attack release control unit that controls a rise and a fall of the multiplier signal based on a time constant determined by the operation device 530 and generates multiplier signals G.sub.LH, G.sub.RH, G.sub.LSH, G.sub.RSH, G.sub.CH, and G.sub.LFEH (all six signals assigned the same value) in the multipliers 10, 11, 12, 13, 14, and 15. The above-mentioned delay units 20 through 25 use a constant value as the delay time that is equivalent to a delay time required for detection of the maximum signal level as mentioned above.

FIG. 8(b) shows a configuration of a gain determination section 50b for "KEY\_LINK2". In this case, the gain determination section comprises a gain determination section 51 to select five signals I.sub.LH, I.sub.RH, I.sub.LSH, I.sub.RSH, and I.sub.CH and a gain determination section 52 to select the I.sub.LFEH signal. The gain determination section 51 detects the maximum signal level value from these five signals, determines a common multiplier signal according to this maximum value, and assigns appropriate values to the multiplier signals G.sub.LH, G.sub.RH, G.sub.LSH, G.sub.RSH, and G.sub.CH. The gain determination section 52 detects the maximum signal level value for the low-band signal I.sub.LFEH to determine the multiplier signal G.sub.LFEH.

FIG. 8(c) shows a configuration of a gain determination section 50c for "KEY\_LINK3". In this case, the gain determination section 50c comprises a gain determination section 53 to select three signals I.sub.LH, I.sub.RH, and I.sub.CH, a gain determination section 54 to select signals I.sub.LSH and I.sub.RSH, and a gain determination section 55 to select the signal I.sub.LFEH. The.gain determination section 53 detects the maximum signal level value from the three signals I.sub.LH, I.sub.RH, and I.sub.CH, determines a common multiplier signal according to this detected value, and assigns appropriate values to the multiplier signals G.sub.LH, G.sub.RSH determine a common signal for the multiplier signals G.sub.LSH and G.sub.RSH. The input signal I.sub.LFEH determines a value for the multiplier signal G.sub.LFEH.

FIG. 8(d) shows a configuration of a gain determination section 50d for "KEY\_LINK4". In this case, the gain determination section 50d comprises a gain determination section 56 to select the two signals I.sub.LH and I.sub.RH, a gain determination section 57 to select the signal I.sub.CH, a gain determination section 58 to select the signals I.sub.LSH and I.sub.RSH, and a gain determination section 59 to select the signal I.sub.LFEH. The gain determination section 56 detects the maximum signal level value from the two signals I.sub.LH and I.sub.RH, determines a common multiplier signal according to this detected value, and assigns appropriate values to the multiplier signals G.sub.LH and G.sub.RH. The other signals

Art Unit: 2615

I.sub.LSH and I.sub.RSH determine a common value for the multiplier signals G.sub.LSH and G.sub.RSH. The signal I.sub.CH determines a value for the multiplier signal G.sub.CH. The signal I.sub.LFEH determines a value for the multiplier signal G.sub.LFEH.

First, the operation device 530 and the like are used to specify parameters such as the key link KEY LINK, the threshold Th. the RATIO, the level values LOW GAIN, MID GAIN, and HI\_GAIN for the corresponding frequency bands, the attack time ATTACK, and the release time RELEASE. When the signals are input, gains for respective frequency bands are determined by the gain determination sections 50, 51, and so on corresponding to the input channels selected by the key link. When KEY LINK1 is selected for high-frequency components, for example, the absolute value and maximum value detection unit 60 peak-holds the maximum value of the input signals within a specified time period. The peak-held value is the maximum value of signal levels (envelopes) of the six input signals. If the peak-held value is smaller than the threshold value Th defined by the operation device 530, the gain control unit 70 assigns the level value HI\_GAIN unchanged as the normal gain NRG as shown in FIG. 4 to the multiplier signal applied to the multipliers 10, 11, 12, 13, 14, and 15. If the peak-held value exceeds the threshold value Th, the normal gain NRG is corrected or adjusted so that the excess level is suppressed in accordance with the RATIO as shown in FIG. 4. The corrected value is assigned to the multiplier signal. The similar process is executed for the low-frequency and medium-frequency components. Specifying the "KNEE" parameter provides a value for the multiplier signal corresponding to the smoothed gain characteristic. That is to say, when the peak-held value is near the threshold Th, the multiplier signal is assigned a value with the smoothed gain characteristic.

At this time, a time difference occurs until detection of the maximum value for the input signals. Accordingly, the delay units 20, 21, 22, 23, 24, and 25 delay the time until the input signal is supplied to the multipliers 10, 11, 12, 13, 14, and 15. On the other hand, the attack release control unit 80 adjusts a rise and a fall of the maximum value for the detected input signal. After the input signal level exceeds the threshold value Th, the attack time ATTACK determines a response until the beginning of compression and is set to the range from several tens of microseconds to approximately 100 milliseconds. After the input signal level goes below the threshold Th, the release time RELEASE determines the time to release the compression and resume the normal gain, and is set to the range from several milliseconds to approximately several seconds.

(2) While the embodiment detects the maximum value from absolute values of the input signals to find the multiplier signal, the present invention is not limited thereto. It may be preferable to find the multiplier signal (amplification) using a value found by integrating absolute values of the input signals or using a square integration value of the input signals.

Art Unit: 2615

The specification essentially discloses determining a maximum for a group and determining a common multiplier signal according to this maximum detected signal and not decreasing the amplification rate as based on the maximum signal detected as recited in the claims. Additionally, the claim language as recited in ambiguous.

## Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Devona E. Faulk whose telephone number is 571-272-7515. The examiner can normally be reached on 8 am - 5 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Vivian Chin can be reached on 571-272-7848. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

VIVIAN CHIN SUPERVICE PATE EXAMINER TECHNOLOGY CENTER 2000

DEF

Application/Control Number: 10/617,186

Art Unit: 2615

Page 6